Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1633	709/231.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:04
L2	1600	718/100.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:04
L3	2146	713/300.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:04
L4	417	713/310.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L5	1198	713/320.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L6	2152	713/321-324.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L7	319	713/330.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L8	665	713/340.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L9	917	719/310.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05

		LASI Searc		/		
L10	371	715/866.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:05
L11	521	340/870.18.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L12	74	714/810.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L13	519	455/103.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L14	9051	709/201-203.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L15	1404	709/200.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L16	28947	709/217-236.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:06
L17	428	maximum near5 transmission near5 power near5 level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:07
L18	13	l17 and signal near5 path near5 gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:07
L19	3996	signal near5 path near5 gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:07

			11115001	·		
L20	525	I19 and error near5 rate	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:08
L21	196	l20 and wireless	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:08
L22	147	l21 and modulation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2006/05/22 15:08
S1	387	signal adj2 interference adj plus adj noise adj ratio	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:28
S2	59	S1 same error adj rate	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:28
S3	22	S2 and wireless and stream\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:34
S4	18	S3 and SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:52
S5	93	BER near3 combin\$6 near3 BER	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:53
S6	0	BER near3 combin\$6 near3 SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:53
S7	21	BER same combin\$6 same SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:53

S8	0	BER near5 combin\$6 near5 SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:54
S9	3	BER near10 combin\$6 near10 SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:56
S10	0	leung-kin.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S11	2	chawla-kapil.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S12	46	leung-kin\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S13	20	chawla-kapil\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S14	17	driessen-peter\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S15	41	qiu-xiaoxin\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:57
S16	40	l11-l15	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:58
S17	107	S11 or S12 or S13 or S14 or S15	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:58

S18	0	S17 and streaming adj service	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 14:58
S19	3	S17 and stream\$5 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:17
S20	43	PER near5 SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:22
S21	43	S20 and wireless	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:24
S22	0	S21 and music	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:22
S23	0	S21 and MPEG4	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:22
S24	0	S20 and error adj based	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:24
S25	7	S20 and error near2 based	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:38
S26	6	link adj adaptation and modulation and coding adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:43
S27	0	predicted adj interference adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:43

		LAST Searc	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	/		
S28	3	predict\$5 near5 interference adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:45
S29	106	(MPEG4 or MPEG adj "4") near5 (AAC or (Advanced adj audio adj coder))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:46
S30	1	S29 and EGPRS	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:47
S31	0	S29 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:47
S32	0	S29 and SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:47
S33	43	S29 and PER	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:48
S34	10	S33 and streaming	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:47
S35	43	S29 and PER	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:50
S36	41	packet adj switched adj bearers	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:54
S37	0	S36 and error near5 concealment near5 technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:51

		LASI Searc		•		
S38	272	error near5 concealment near5 technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:51
S39	215	error adj concealment adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:51
S40	21	S39 and receiving adj end	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:52
S41	4	S39 same receiving adj end	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:52
S42	6	S36 same stream\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 15:57
S43	9	EGPRS and power adj3 technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 16:03
S44	1	EGPRS and signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 16:04
S45	2	SINR same signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 16:08
S46	3	SINR and signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 16:10
S47	. 8	SINR same path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 16:20

	,					
S48	1	("6374117").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 17:14
S49	1	("6760313").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 17:32
S50	. 0	music adj delivery adj service and SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:33
S51	44	music adj delivery adj service	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:36
S52	3	S51 and cellular	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:33
S53	0	S51 and MPEG4	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:34
S54	1	S51 and MPEG adj "4"	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:34
S55	10	S51 and wireless	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 17:51
S56	1	("6856812").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 17:57
S57	1	("6282209").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 18:19
S58	1	("5901186").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 18:26
S59	2	(("5901186") or ("6,760,313")).PN.	US-PGPUB; USPAT	OR	OFF	2005/10/24 18:28
S60	19	interval same power adj control adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:28

		LAST Searc		/		
S61	19	S60 and intervals same power adj control adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:28
S62	2	S60 and intervals same power adj control adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:34
S63	0	intervals same link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:35
S64	0	periodic same link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:35
S65	8	intervals and link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:37
S66	29	intervals and link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:37
S67	0	intervals same periodic and link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:37
S68	5	intervals and periodic and link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:43
S69	61	link adj adaptation adj technique	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:43
S70	1130612	S69 and period\$5 or interval	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:43

S71	47	S69 and (period\$5 or interval)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:43
S72	33	S69 and (periodic or interval)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:44
S73	9	S69 and (periodic)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:45
S74	24	S72 not S73	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:51
S75	230	signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/10/24 18:51
S76	197	signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:51
S77	4	S76 and transmission adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:52
S78	2647208	S77 and predicted adj interference adj power level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:52
S79	4	S77 and (predicted adj interference adj power level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:53
S80	0	S77 and (predicted adj interference adj power adj level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:53

S81	0	(predicted adj interference adj power adj level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:53
S82	140	(interference adj power adj level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:53
S83	1	S77 and (interference adj power adj level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 18:59
S84	2	predict\$5 near5 (interference adj power adj level)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:08
S85	79	maximum adj transmission adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:10
S86	1	S85 and SINR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:09
S87	42	S85 and wireless	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:09
S88	3	S87 and signal adj path	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:09
S89	3	(US-20050135312-\$).did. or (US-6952181-\$ or US-6657214-\$). did.	US-PGPUB; USPAT	OR	ON	2005/10/24 19:10
S90	3	S89 and maximum adj transmission adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:24

S91	55	SIPNR	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:24
S92	192	signal adj interference adj plus adj noise adj ratio	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:33
S93	94	S92 and error adj rate	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:27
S94	0	S93 and signal adj path adj gain	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:26
S95	1	S93 and maximum adj transmission adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:26
S96	13	S93 and predict\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:27
S97	13	(US-20050068922-\$ or US-20040208251-\$ or US-20030086366-\$ or US-20020186761-\$ or US-20020093926-\$ or US-20020075830-\$ or US-20020067761-\$).did. or (US-6882678-\$ or US-6463295-\$ or US-6389066-\$ or US-6215827-\$ or US-6108374-\$ or US-5886988-\$). did.	US-PGPUB; USPAT	OR	ON	2005/10/24 19:45
S98	13	S97 and signal adj interference adj plus adj noise adj ratio	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF.	2005/10/24 19:43
S99	4	divid\$5 same interference adj power adj level	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/10/24 19:44

				T	т	
S10 0	11	S92 near5 estimat\$5	US-PGPUB; USPAT	OR	ON	2005/10/24 19:45
S10 1	1	("5778224").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/26 16:02
S10 2	1	("5799173").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/26 16:02
S10 3	1	("6044225").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/26 20:20
S10 4	1	("6223274").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/27 17:56
S10 5	1	("6,751,663").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/27 17:56
S10 6	1	("6,625,657").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/27 17:57
S10 7	1	("6,405,251").PN.	US-PGPUB; USPAT	OR	OFF	2005/10/27 17:57
S10 8	4981	leung\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:19
S10 9	47	leung-kin\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:19
S11 0	20	chawla-kapil\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:19
S11 1	17	driessen-peter\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:20
S11 2	1	qui-xiaoxin\$.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:20
S11 3	8732	at&t\$.as.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:20

		,				
S11 4	8784	S109 or S110 or S111 or S112 or S113	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:20
S11 5	4	S114 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:24
S11 6	158	S114 and power adj control\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:25
S11 7	0	S116 and signal adj to adj noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:21
S11 8	0	S116 and signal adj to adj2 noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:25
S11 9	29	S116 and signal adj3 noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:23
S12 0	7888	709/230-238.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:23
S12 1	1330	709/200.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:23
S12 2	0	"709".201-203.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:24
S12 3	8278	709/201-203.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:24

			T	, T	Т	
\$12 4	22263	709/217-229.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:24
S12 5	32560	S120 or S121 or S123 or S124	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:24
S12 6	11	S125 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:31
S12 7	347	S125 and power adj control\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:31
S12 8	0	S126 and signal adj to adj2 noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:25
S12 9	0	S127 and signal adj to adj2 noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:25
S13 0	32	S127 and signal adj3 noise	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26
S13 1	1281	370/329.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26
S13 2	2469	370/252.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26
S13 3	506	370/310.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26

		1			·	
S13 4	1388	370/328.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26
S13 5	1281	370/329.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:26
S13 6	1144	370/331.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S13 7	634	370/332.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S13 8	178	370/333.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S13 9	209	370/334.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S14 0	288	370/341.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S14 1	384	370/431.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S14 2	1787	370/465.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:27
S14 3	1906	370/468.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:29

S14 4	1640	455/423-425.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:30
S14 5	4133	455/434,450-453,464,509,510.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:30
S14 6	15803	S131 or S132 or S133 or S134 or S135 or S136 or S137 or S138 or S139 or S140 or S141 or S142 or S143 or S144 or S145	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:31
S14 7	172	S146 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:35
S14 8	73	S147 and power adj control\$5	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:32
S14 9	0	364/574,572.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:32
S15 0	0	364/574.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:32
S15 1	0	364/572.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:33
S15 2	421	375/262.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:33
S15 3	5039	375/262,265,325,340,341,261,296, 272,303,325,340,341.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:40

			,		,	,
S15 4	5039	S152 or S153	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:34
S15 5	12	S154 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:41
S15 6	2140	714/791-795.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:36
S15 7	0	S156 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:36
S15 8	3989	375/130,144,346,347.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:41
S15 9	7	S158 and link adj adaptation	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/11/08 19:41

window

Subscribe (Full Service) Register (Limited Service, Free) Login

Search: • The ACM Digital Library The Guide

+signal +path +maximum +transmission +power +modulation



HE ACK DICH IAL ILHSIRARY

Feedback Report a problem Satisfaction survey

Terms used signal path maximum transmission power modulation wireless

Found 394 of 176.279

Sort results

Best 200 shown

Display

results

 \triangle relevance expanded form

Save results to a Binder Mar Open results in a new

Try an Advanced Search Try this search in The ACM Guide

Results 1 - 20 of 200

Result page: 1 2 3 4 5 6 7 8 9 10

Relevance scale

Energy Awareness and Power Control: Minimum energy paths for reliable

communication in multi-hop wireless networks

Suman Banerjee, Archan Misra June 2002 Proceedings of the 3rd ACM international symposium on Mobile ad hoc networking & computing

Publisher: ACM Press


Full text available: pdf(189.29 KB)

Additional Information: full citation, abstract, references, citings, index terms

Current algorithms for minimum-energy routing in wireless networks typically select minimum-cost multi-hop paths. In scenarios where the transmission power is fixed, each link has the same cost and the minimum-hop path is selected. In situations where the transmission power can be varied with the distance of the link, the link cost is higher for longer hops; the energy-aware routing algorithms select a path with a large number of small-distance hops. In this paper, we argue that such a formulati ...

Keywords: ad-hoc networks, energy efficiency, routing

Wireless intraoffice networks



July 1988 ACM Transactions on Information Systems (TOIS), Volume 6 Issue 3


Publisher: ACM Press

Full text available: pdf(1.98 MB)

Additional Information: full citation, abstract, references, citings, index terms, review

An overview of the existing and growing demands for wireless office information networks is provided, and the existing research activities are assessed in some detail. The radio frequency (RF) and infrared (IR) communication technologies are examined as candidates for wireless intraoffice communications. The available bandwidths, according to federal regulations and characteristics of the channel for RF communications, are given. Digital narrow-band and wideband spread-spectrum RF communica ...

3 Wireless LAN optimizations: MiSer: an optimal low-energy transmission strategy for



Daji Qiao, Sunghyun Choi, Amit Jain, Kang G. Shin

September 2003 Proceedings of the 9th annual international conference on Mobile computing and networking

Publisher: ACM Press

Full text available: pdf(248.70 KB)

Additional Information: full citation, abstract, references, citings, index terms

Reducing the energy consumption by wireless communication devices is perhaps the most important issue in the widely-deployed and exponentially-growing IEEE 802.11 Wireless LANs (WLANs). TPC (Transmit Power Control) and PHY (physical layer) rate adaptation have been recognized as two most effective ways to achieve this goal. The emerging 802.11h standard, which is an extension to the current 802.11 MAC and the high-speed 802.11a PHY, will provide a structured means to support intelligent TPC.In t ...

Keywords: IEEE 802.11a/h, MiSer, PHY rate adaptation, TPC

PARO: supporting dynamic power controlled routing in wireless ad hoc networks Javier Gomez, Andrew T. Campbell, Mahmoud Naghshineh, Chatschik Bisdikian September 2003 Wireless Networks, Volume 9 Issue 5

Publisher: Kluwer Academic Publishers

Full text available: pdf(311.95 KB)

Additional Information: full citation, abstract, references, citings, index terms

This paper introduces PARO, a dynamic power controlled routing scheme that helps to minimize the transmission power needed to forward packets between wireless devices in ad hoc networks. Using PARO, one or more intermediate nodes called "redirectors" elects to forward packets on behalf of source-destination pairs thus reducing the aggregate transmission power consumed by wireless devices. PARO is applicable to a number of networking environments including wireless sensor networks, home networks ...

Keywords: ad hoc networks, power control, power optimization, routing protocols

5 Link and channel measurement: A simple mechanism for capturing and replaying





Glenn Judd, Peter Steenkiste

August 2005 Proceeding of the 2005 ACM SIGCOMM workshop on Experimental approaches to wireless network design and analysis E-WIND '05

Publisher: ACM Press

Full text available: pdf(6.06 MB)

Additional Information: full citation, abstract, references, index terms

Physical layer wireless network emulation has the potential to be a powerful experimental tool. An important challenge in physical emulation, and traditional simulation, is to accurately model the wireless channel. In this paper we examine the possibility of using on-card signal strength measurements to capture wireless channel traces. A key advantage of this approach is the simplicity and ubiquity with which these measurements can be obtained since virtually all wireless devices provide the req ...

Keywords: channel capture, emulation, wireless

6 <u>Wide-band TD-CDMA MAC with minimum-power allocation and rate- and BER-scheduling for wireless multimedia networks</u>



Xudong Wang

February 2004 IEEE/ACM Transactions on Networking (TON), Volume 12 Issue 1

Publisher: IEEE Press

Full text available: pdf(523.38 KB) Additional Information: full citation, abstract, references, index terms

A wide-band time-division-code-division multiple-access (TD-CDMA) medium access control (MAC) protocol is introduced in this paper. A new minimum-power allocation algorithm is developed to minimize the interference experienced by a code channel such that heterogeneous bit-error rate (BER) requirements of multimedia traffic are satisfied. Further, from analysis of the maximum capacity of a time slot, it is concluded that both rate and BER scheduling are necessary to reach a maximum capacity. Base ...

Keywords: bit-error rate (BER), medium access control (MAC), minimum-power allocation, quality of service (QoS), wide-band TD-CDMA

7 Resource Control and QoS in Wireless Systems: Resource control for elastic traffic in



6 9

CDMA networks

Vasilios A. Siris

September 2002 Proceedings of the 8th annual international conference on Mobile computing and networking

Publisher: ACM Press

Full text available: pdf(467.48 KB)

Additional Information: <u>full citation</u>, <u>abstract</u>, <u>references</u>, <u>citings</u>, <u>index</u>

We present a framework for resource control in CDMA networks carrying elastic traffic, considering both the uplink and the downlink direction. The framework is based on microeconomics and congestion pricing, and seeks to exploit the joint control of the transmission rate and the signal quality in order to achieve efficient utilization of network resources, in a distributed and decentralized manner. An important feature of the

Keywords: congestion pricing, radio resource management, rate control, utility functions, wireless/wired integration

framework is that it incorporates both the congestion for shared resou ...

8 <u>Signal design and system operation of Globalstar versus IS-95 CDMA—similarities</u> and differences



Leonard Schiff, A. Chockalingam

January 2000 Wireless Networks, Volume 6 Issue 1

Publisher: Kluwer Academic Publishers

Full text available: pdf(273.24 KB) Additional Information: full citation, abstract, references, index terms

The Globalstar^{TM} system provides telephone and data services to and from mobile and fixed users in the area between ± 70 degrees latitude. Connection between user terminals and the PSTN is established through fixed terrestrial gateways via a constellation of low earth orbiting (LEO) satellites. Globalstar uses an extension of the IS‐ 95 CDMA standard that is used in terrestrial digital cellular systems. The LEO satellite link is ...

9 Low power converter circuits: 2.45 GHz power and data transmission for a low-power





autonomous sensors platform

Stefano Gregori, Yunlei Li, Huijuan Li, Jin Liu, Franco Maloberti

August 2004 Proceedings of the 2004 international symposium on Low power electronics and design

Publisher: ACM Press

Full text available: pdf(710.58 KB) Additional Information: full citation, abstract, references, index terms

This paper describes a power conversion and data recovery system for a microwave powered sensor platform. A patch microwave antenna, a matching filter and a rectifier make the system frontend and implement the RF-to-DC conversion of power carrier. The efficiency of the power conversion is as high as 47% with an input power level 250 μW at 2.45 GHz. Then, a 0.18 μm CMOS integrated circuit extracts the clock and the digital data. A modified pulse amplitude modulation scheme is used to modulate the ...

Keywords: RF to DC power conversion, low power clock and data recovery, microwave power transmission, wireless sensor

10 Mobile power management for wireless communication networks

John M. Rulnick, Nicholas Bambos

March 1997 Wireless Networks, Volume 3 Issue 1

Publisher: Kluwer Academic Publishers


Additional Information: full citation, abstract, references, citings, index

Full text available: pdf(274.39 KB)

terms, review

For fixed quality-of-service constraints and varying channel interference, how should a mobile node in a wireless network adjust its transmitter power so that energy consumption is minimized? Several transmission schemes are considered, and optimal solutions are obtained for channels with stationary, extraneous interference. A simple dynamic power management algorithm based on these solutions is developed. The algorithm is tested by a series of simulations, including the extraneous-interfer ...

11 Routing 1: Efficient geographic routing in multihop wireless networks



May 2005 Proceedings of the 6th ACM international symposium on Mobile ad hoc networking and computing MobiHoc '05

Publisher: ACM Press

Full text available: Top pdf(257.99 KB) Additional Information: full citation, abstract, references, index terms

We propose a new link metric called normalized advance (NADV) for geographic routing in multihop wireless networks. NADV selects neighbors with the optimal trade-off between proximity and link cost. Coupled with the local next hop decision in geographic routing, NADV enables an adaptive and efficient cost-aware routing strategy. Depending on the objective or message priority, applications can use the NADV framework to minimize various types of link cost. We present efficient methods for li ...

Keywords: geographic routing, link cost estimation, routing metric, wireless multihop networks

12 Best poster papers from MobiHoc 2002: An on-demand minimum energy routing

protocol for a wireless ad hoc network

Sheetalkumar Doshi, Shweta Bhandare, Timothy X Brown

June 2002 ACM SIGMOBILE Mobile Computing and Communications Review, Volume 6 Issue 3


Publisher: ACM Press

Full text available: pdf(203.93 KB)

Additional Information: full citation, abstract, references, citings, index terms

A minimum energy routing protocol reduces the energy consumption of the nodes in a wireless ad hoc network by routing packets on routes that consume the minimum amount of energy to get the packets to their destination. This paper identifies the necessary features of an on-demand minimum energy routing protocol and suggests mechanisms for their implementation. We highlight the importance of efficient caching techniques to store the minimum energy route information and propose the use of an ...

13 Networking experience: Understanding packet delivery performance in dense



Jerry Zhao, Ramesh Govindan

November 2003 Proceedings of the 1st international conference on Embedded networked sensor systems

Publisher: ACM Press

Additional Information: full citation, abstract, references, citings, index Full text available: pdf(501.89 KB) terms

Wireless sensor networks promise fine-grain monitoring in a wide variety of environments. Many of these environments (e.g., indoor environments or habitats) can be harsh for wireless communication. From a networking perspective, the most basic aspect of wireless communication is the packet delivery performance: the spatio-temporal characteristics of packet loss, and its environmental dependence. These factors will deeply impact the performance of data acquisition from these networks. In th ...

Keywords: low power radio, packet loss, performance measurement



14 SpectrumWare: a software-oriented approach to wireless signal processing

David L. Tennenhouse, Vanu G. Bose

December 1995 Proceedings of the 1st annual international conference on Mobile computing and networking

Publisher: ACM Press

Full text available: pdf(1.29 MB) Additional Information: full citation, references, index terms

15 Routing optimizations: Minimum energy disjoint path routing in wireless ad-hoc

networks

Anand Srinivas, Eytan Modiano

September 2003 Proceedings of the 9th annual international conference on Mobile computing and networking

Publisher: ACM Press

Full text available: pdf(452.89 KB)

Additional Information: full citation, abstract, references, citings, index terms

We develop algorithms for finding minimum energy disjoint paths in an all-wireless network, for both the node and link-disjoint cases. Our major results include a novel polynomial time algorithm that optimally solves the minimum energy 2 link-disjoint paths problem, as well as a polynomial time algorithm for the minimum energy k node-disjoint paths problem. In addition, we present efficient heuristic algorithms for both problems. Our results show that link-disjoint paths consume substantially le ...

Keywords: disjoint paths, distributed algorithms, energy efficiency, minimum energy, multipath routing, wireless ad-hoc networks

16 A rate-adaptive MAC protocol for multi-Hop wireless networks

Gavin Holland, Nitin Vaidya, Paramvir Bahl

July 2001 Proceedings of the 7th annual international conference on Mobile computing and networking

Publisher: ACM Press

Full text available: pdf(467.95 KB)

Additional Information: full citation, abstract, references, citings, index terms

Wireless local area networks (W-LANs) have become increasingly popular due to the recent availability of affordable devices that are capable of communicating at high data rates. These high rates are possible, in part, through new modulation schemes that are optimized for the channel conditions bringing about a dramatic increase in bandwidth efficiency. Since the choice of which modulation scheme to use depends on the current state of the transmission channel, newer wireless devices often supp ...

17 The SpectrumWare approach to wireless signal processing

David L. Tennenhouse, Vanu G. Bose

March 1996 Wireless Networks, Volume 2 Issue 1

Publisher: Kluwer Academic Publishers

Full text available: pdf(1.18 MB)

Additional Information: full citation, abstract, references, citings, index terms

The SpectrumWare project is applying a software oriented approach to wireless communication and distributed signal processing. Advances in processor and analog-to-digital conversion technology have made it possible to implement virtual radios that directly sample wide bands of the RF spectrum and process these samples in application software. The elimination of dedicated hardware introduces tremendous flexibility into a wireless communication system. Our approach goes further than the softw ...

MR²RP: the multi-rate and multi-range routing protocol for IEEE 802.11 ad hoc wireless networks

Shiann-Tsong Sheu, Yihjia Tsai, Jenhui Chen

March 2003 Wireless Networks, Volume 9 Issue 2

Publisher: Kluwer Academic Publishers

Full text available: pdf(252.69 KB) Additional Information: full citation, abstract, references, index terms

This paper discusses the issue of routing packets over an IEEE 802.11 *ad hoc* wireless network with multiple data rates (1/2/5.5/11 Mb/s). With the characteristics of modulation schemes, the data rate of wireless network is inversely proportional with the transmission distance. The conventional shortest path of minimum-hops approach will be no longer suitable for the contemporary multi-rate/multi-range wireless networks (MR²WN). In this paper, we will propose an efficient delay- ...

Keywords: ad hoc, local area network (LAN), medium access control (MAC), routing, wireless

19 <u>CyPhone—bringing augmented reality to next generation mobile phones</u>

Tino Pyssysalo, Tapio Repo, Tuukka Turunen, Teemu Lankila, Juha Röning April 2000 **Proceedings of DARE 2000 on Designing augmented reality environments Publisher:** ACM Press

Full text available: pdf(6.46 MB)

Additional Information: full citation, abstract, references, index terms

We describe a prototype implementation of a future mobile phone called CyPhone. In addition to voice calls, it has been designed to support context-specific and multi-user multimedia services in an augmented reality manner. Context-awareness has been implemented with GPS-based navigation techniques and a registration algorithm, capable of detecting a predefined 3-D model or a landmark in the environment. A new adaptive transport protocol has been developed to support real-time packet-switched ...

Keywords: mobile communication, navigation, networked virtual reality, real-time data transport protocols, registration

20 Interference in wireless multi-hop ad-hoc networks and its effect on network capacity

Ramin Hekmat, Piet Van Mieghem

July 2004 Wireless Networks, Volume 10 Issue 4

Publisher: Kluwer Academic Publishers

Full text available: pdf(552.50 KB) Additional Information: full citation, abstract, references, index terms

In this paper we propose a new model to calculate interference levels in wireless multihop ad-hoc networks. This model computes the expected value of Carrier to Interference ratio (C/I) by taking into account the number of nodes, density of nodes, radio propagation aspects, multi-hop characteristics of the network, and the amount of relay traffic. The expected values of C/I are used to determine network capacity and data throughput per node. Our model uses a regular lattice for po ...

Keywords: ad-hoc networks, analytical methods, interference, modelling, sensor networks, throughput

Results 1 - 20 of 200 Result page: 1 2 3 4 5 6 7 8 9 10 next

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2006 ACM, Inc.

<u>Terms of Usage Privacy Policy Code of Ethics Contact Us</u>

Useful downloads: Adobe Acrobat QuickTime Windows Media Player Real Player



Welcome United States Patent and Trademark Office

□ Search Results

BROWSE

SEARCH

IEEE XPLORE GUIDE

SUPPORT

e-mail printer friendly

Results for "((wireless<in>metadata) <and> (modulation<in>metadata))<and> (power&l..."

Your search matched 1530 of 1351118 documents.

A maximum of 100 results are displayed, 25 to a page, sorted by Relevance in Descending order.

» Search Options

View Session History

New Search

» Other Resources (Available For Purchase)

Top Book Results

RF Technologies for Low-Power Wireless Communications by Itoh, T.; Haddad, G.; Harvey, J.; Hardcover, Edition: 1

Theory of Code Division Multiple Access Communication by Zigangirov, K. S.; Hardcover, Edition: 1

Wireless Communications in the 21st Century

by Shafi, M.; Ogose, S.; Hattori, T.; Hardcover, Edition: 1

View All 3 Result(s)

» Key

IEEE JNL IEEE Journal or

Magazine

IEE JNL IEE Journal or Magazine

IEEE CNF IEEE Conference

Proceeding

IEE CNF IEE Conference

Proceeding

IEEE STD IEEE Standard

Modify Search

((wireless<in>metadata) <and> (modulation<in>metadata))<and> (power<in>me

Search >

Check to search only within this results set

Display Format:

© Citation © Citation & Abstract

view selected items

Select All Deselect All

View: 1-25 | 26-50 | 51-75 | 76-100

 Power minimization under throughput management over wireless networks with antenna diversity

Zhu Han; Liu, K.J.R.;

Wireless Communications, IEEE Transactions on Volume 3, Issue 6, Nov. 2004 Page(s):2170 - 2181 Digital Object Identifier 10.1109/TWC.2004.837431

AbstractPlus | References | Full Text: PDF(464 KB) | IEEE JNL

Rights and Permissions

2. Ultra low-power radio design for wireless sensor networks

Enz, C.; Scolari, N.; Yodprasit, U.;

Radio-Frequency Integration Technology: Integrated Circuits for Wideband Communication and

Wireless Sensor Networks, 2005. Proceedings. 2005 IEEE International Workshop on

30 Nov.-2 Dec. 2005 Page(s):1 - 17

Digital Object Identifier 10.1109/RFIT.2005.1598863

AbstractPlus | Full Text: PDF(9224 KB) IEEE CNF

Rights and Permissions

3. Advanced frequency hopping modulation for spread spectrum WLAN

Glisic, S.; Nikolic, Z.; Milosevic, N.; Pouttu, A.;

Selected Areas in Communications, IEEE Journal on

Volume 18, Issue 1, Jan. 2000 Page(s):16 - 29

Digital Object Identifier 10.1109/49.821702

AbstractPlus | References | Full Text: PDF(400 KB) | IEEE JNL

Rights and Permissions

4. Design issues of ultra-wideband systems for high-rate wireless PANs: modulation schemes and coexistence with WLANs

Jeong-Heon Lee; Tae-Jin Lee;

Wireless Communication Technology, 2003. IEEE Topical Conference on

15-17 Oct. 2003 Page(s):459 - 460

Digital Object Identifier 10.1109/WCT.2003.1321603

AbstractPlus | Full Text: PDF(233 KB) | IEEE CNF

Rights and Permissions

5. Effect of power amplifier impairments in designing OFDM based wireless communication system

Liu, J.; Arslan, H.; Dunleavy, L.P.;

Wireless Communication Technology, 2003. IEEE Topical Conference on

15-17 Oct. 2003 Page(s):33 - 34

Digital Object Identifier 10.1109/WCT.2003.1321430

AbstractPlus | Full Text: PDF(274 KB) IEEE CNF

Rights and Permissions

6. Adaptive modulation, adaptive coding, and power control for fixed cellular broadband wireless systems: some new insights

Armanious, E.; Falconer, D.D.; Yanikomeroglu, H.;

Wireless Communications and Networking, 2003. WCNC 2003. 2003 IEEE

Volume 1, 16-20 March 2003 Page(s):238 - 242 vol.1

Digital Object Identifier 10.1109/WCNC.2003.1200352

AbstractPlus | Full Text: PDF(393 KB) | IEEE CNF

Rights and Permissions

7. Modulation scaling for real-time energy aware packet scheduling

Schurgers, C.; Raghunathan, V.; Srivastava, M.B.;

Global Telecommunications Conference, 2001. GLOBECOM '01. IEEE

Volume 6, 25-29 Nov. 2001 Page(s):3653 - 3657 vol.6

Digital Object Identifier 10.1109/GLOCOM.2001.966363

AbstractPlus | Full Text: PDF(205 KB) | IEEE CNF

Rights and Permissions

8. A Digitally Controlled Constant Envelope Phase-Shift Modulator for Low-Power Broad-Band Wireless Applications

Yang, X.; Lin, J.;

Microwave Theory and Techniques, IEEE Transactions on

Volume 54, Issue 1, Jan. 2006 Page(s):96 - 105

Digital Object Identifier 10.1109/TMTT.2005.861669

AbstractPlus | Full Text: PDF(552 KB) IEEE JNL

Rights and Permissions

9. Analysis of microwave MESFET power amplifiers for digital wireless communications systems

Chien-Chang Huang; Han-Ting Pai; Kuan-Yu Chen;

Microwave Theory and Techniques, IEEE Transactions on

Volume 52, Issue 4, April 2004 Page(s):1284 - 1291

Digital Object Identifier 10.1109/TMTT.2004.825646

AbstractPlus | References | Full Text: PDF(488 KB) | IEEE JNL

Rights and Permissions

10. An adaptive code position modulation scheme for wireless sensor networks

Yong Yuan; Zongkai Yang; Jianhua He; Wenqing Chen;

Communications Letters, IEEE

Volume 9, Issue 6, Jun 2005 Page(s):481 - 483

Digital Object Identifier 10.1109/LCOMM.2005.06003

AbstractPlus | Full Text: PDF(914 KB) | IEEE JNL

Rights and Permissions

11. Energy efficient source coding and modulation for wireless applications

Prakash, Y.; Gupta, S.K.S.;

Wireless Communications and Networking, 2003. WCNC 2003. 2003 IEEE

Volume 1, 16-20 March 2003 Page(s):212 - 217 vol.1

Digital Object Identifier 10.1109/WCNC.2003.1200347

AbstractPlus | Full Text: PDF(261 KB) | IEEE CNF

Rights and Permissions

12. Power minimization under constant throughput constraint in wireless networks with beamforming

Han, Z.; Liu, K.J.R.;

Vehicular Technology Conference, 2002. Proceedings. VTC 2002-Fall. 2002 IEEE 56th

Volume 1, 24-28 Sept. 2002 Page(s):611 - 615 vol.1

Digital Object Identifier 10.1109/VETECF.2002.1040417

AbstractPlus | Full Text: PDF(306 KB) IEEE CNF

Rights and Permissions

	13. Modulation scaling for energy aware communication systems Schurgers, C.; Aberthorne, O.; Srivastava, M.B.; Low Power Electronics and Design, International Symposium on, 2001. 6-7 Aug. 2001 Page(s):96 - 99 Digital Object Identifier 10.1109/LPE.2001.945382 AbstractPlus Full Text: PDF(348 KB) IEEE CNF Rights and Permissions
	14. Outage in adaptive wireless communication systems Kamath, K.M.; Goeckel, D.L.; Signals, Systems and Computers, 2001. Conference Record of the Thirty-Fifth Asilomar Conference on Volume 2, 4-7 Nov. 2001 Page(s):1031 - 1035 vol.2 Digital Object Identifier 10.1109/ACSSC.2001.987651 AbstractPlus Full Text: PDF(455 KB) IEEE CNF
	Rights and Permissions
	15. Study on wideband CDMA modulation, power control and wireless access for CDMA multimedia systems Ling Qiu; Pengfei Xia; Jinkang Zhu; Vehicular Technology Conference, 1999. VTC 1999 - Fall. IEEE VTS 50th Volume 5, 19-22 Sept. 1999 Page(s):2944 - 2948 vol.5 Digital Object Identifier 10.1109/VETECF.1999.800326 AbstractPlus Full Text: PDF(284 KB) IEEE CNF
	Rights and Permissions
	16. Differential pulse position modulation for power-efficient wireless infrared communication Da-Shan Shiu; Kahn, J.M.; Global Telecommunications Conference, 1998. GLOBECOM 98. The Bridge to Global Integration. IEEE Volume 1, 8-12 Nov. 1998 Page(s):219 - 224 vol.1 Digital Object Identifier 10.1109/GLOCOM.1998.775727 AbstractPlus Full Text: PDF(288 KB) IEEE CNF Rights and Permissions
	17. Performance evaluation of a multicarrier modulation technique allowing strongly nonlinear amplification Dinis, R.; Gusmao, A.; Communications, 1998. ICC 98. Conference Record.1998 IEEE International Conference on Volume 2, 7-11 June 1998 Page(s):791 - 796 vol.2 Digital Object Identifier 10.1109/ICC.1998.685118 AbstractPlus Full Text: PDF(516 KB) IEEE CNF Rights and Permissions
	18. Adaptive modulation system with discrete power control and predistortion-type nonlinear compensation for high spectral efficient and high power efficient wireless communication systems Arimochi, K.; Sampei, S.; Morinaga, N.; Personal, Indoor and Mobile Radio Communications, 1997. 'Waves of the Year 2000'. PIMRC '97., The 8th IEEE International Symposium on Volume 2, 1-4 Sept. 1997 Page(s):472 - 476 vol.2 Digital Object Identifier 10.1109/PIMRC.1997.631045 AbstractPlus Full Text: PDF(492 KB) IEEE CNF Rights and Permissions
Б	19. Low BER radio design for wireless local loop applications Merenda, J.L.; Pierro, J.; Clouse, R.; Gunther, J.; Fenniman, C.; ELECTRO '96. Professional Program. Proceedings. 30 April-2 May 1996 Page(s):245 - 251 Digital Object Identifier 10.1109/ELECTR.1996.501235 AbstractPlus Full Text: PDF(360 KB) IEEE CNF Rights and Permissions

20. A comparison of different wireless LAN transmission techniques using ray tracing

Falsafi, A.; Pahlavan, K.; Ganing Yang;

Personal, Indoor and Mobile Radio Communications, 1995. PIMRC'95. 'Wireless: Merging onto the Information Superhighway'., Sixth IEEE International Symposium on

Volume 3, 27-29 Sept. 1995 Page(s):1062

Digital Object Identifier 10.1109/PIMRC.1995.477311

AbstractPlus | Full Text: PDF(516 KB) | IEEE CNF

Rights and Permissions

21. Reconfigurable digital baseband modulation for wireless computer communication

Brown, C.; Feher, K.;

Computers and Communications, 1995. Conference Proceedings of the 1995 IEEE Fourteenth

Annual International Phoenix Conference on

28-31 March 1995 Page(s):610 - 616

Digital Object Identifier 10.1109/PCCC.1995.472430

AbstractPlus | Full Text: PDF(476 KB) | IEEE CNF

Rights and Permissions

22. Multiple-subcarrier modulation for non-directed wireless infrared communication

Carruthers, J.B.; Kahn, J.M.;

Global Telecommunications Conference, 1994. GLOBECOM '94. 'Communications: The Global

Bridge'., IEEE

Volume 2, 28 Nov.-2 Dec. 1994 Page(s):1055 - 1059 vol.2

Digital Object Identifier 10.1109/GLOCOM.1994.512819

AbstractPlus | Full Text: PDF(472 KB) | IEEE CNF

Rights and Permissions

23. Performance enhancement of adaptive orthogonal modulation in wireless CDMA systems

Muqattash, A.; Krunz, M.; Tao Shu;

Selected Areas in Communications, IEEE Journal on

Volume 24, Issue 3, March 2006 Page(s):565 - 578

Digital Object Identifier 10.1109/JSAC.2005.862406

AbstractPlus | Full Text: PDF(608 KB) | IEEE JNL

Rights and Permissions

24. On the RF/DSP design for efficiency of OFDM transmitters

Helaoui, M.; Boumaiza, S.; Ghazel, A.; Ghannouchi, F.M.;

Microwave Theory and Techniques, IEEE Transactions on

Volume 53, Issue 7, July 2005 Page(s):2355 - 2361

Digital Object Identifier 10.1109/TMTT.2005.850437

AbstractPlus | Full Text: PDF(552 KB) | IEEE JNL

Rights and Permissions

25. Performance of wireless CDMA with M-ary orthogonal modulation and cell site antenna arrays

Naguib, A.F.; Paulraj, A.;

Selected Areas in Communications, IEEE Journal on

Volume 14, Issue 9, Dec. 1996 Page(s):1770 - 1783

Digital Object Identifier 10.1109/49.545700

AbstractPlus | References | Full Text: PDF(1144 KB) | IEEE JNL

Rights and Permissions

View: 1-25 | 26-50 | 51-75 | 76-100

Help Contact Us Privacy & Security IEEE.org

© Copyright 2006 IEEE - All Rights Reserved

नि Inspec

Sign in



 Web
 Images
 Groups
 News
 Froogle
 Maps
 more »

 signal path maximum transmission power mod
 Search
 Advanced Search Preferences

Web Results 1 - 10 of about 448,000 for signal path maximum transmission power modulation wireless. (0.25 seconds)

OFDM as a modulation technique for wireless communications, with a ...

Attenuation is the drop in the **signal power** when transmitting from one point to another. It can be caused by the **transmission path** length, obstructions in ... www.skydsp.com/publications/4thyrthesis/chapter1.htm - 63k - <u>Cached</u> - <u>Similar pages</u>

[PDF] Challenges in Multihop Wireless Networks

File Format: PDF/Adobe Acrobat - View as HTML

How should **transmission power** and **modulation** scheme be selected at each ... has fading and shadowing in addition to **signal** attenuation (**path** loss) ... www.eurongi2006.upv.es/download/ Catherine Rosenberg NGI2006.pdf - Similar pages

Wireless

Because there may be no direct **path** for the incident **signal** in ... LMDS systems have a typical **maximum transmission** range of approximately 3 miles, ... www.cisco.com/univercd/cc/ td/doc/cisintwk/ito_doc/wireless.htm - 142k - Cached - Similar pages

Novel Approach Yields 100mW Bluetooth Amplifier - Maxim/Dallas

The minimum transmit output power is 0dBm, whereas the maximum transmit output power ... This PA approach provides only the RF signal path, basic biasing, ... www.maxim-ic.com/appnotes.cfm/appnote_number/732/ - 48k - Cached - Similar pages

Citations: A Kalman-filter method for power control in broadband ...

In turn, without knowing the **modulation** level, the **transmission power** cannot be ... Thus, the SINR can be predicted from the **path** gain, the **maximum power**, citeseer.ist.psu.edu/context/1288665/328611 - 17k - <u>Cached</u> - <u>Similar pages</u>

[PPT] S-72.244 Modulation and coding methods

File Format: Microsoft Powerpoint 97 - View as HTML

Therefore, in general, **wireless** systems may maintain **signal** energy longer that wired systems. However, actual received **power** depends greatly on **transmission** ... www.comlab.hut.fi/opetus/245/2004/02_channels.ppt - <u>Similar pages</u>

[PPT] S-72.244 Modulation and coding methods

File Format: Microsoft Powerpoint 97 - View as HTML

... devices that are part of the **transmission path** followed by a **signal** ... Therefore, in general, **wireless** systems may maintain **signal** energy longer that ... www.comlab.hut.fi/studies/1140/02 1140 channels.ppt - Similar pages

[PDF] Diploma theses at the Communications Lab in Wintersemester 2005/06

File Format: PDF/Adobe Acrobat

Many broadband wireless transmission systems like eg IEEE 802.11a employ orthogonal ... constraints on the available **signal power** and required data rate. ... www.uni-kassel.de/fb16/hfk/neu/mastertheses.pdf - <u>Similar pages</u>

Linksys White Papers

802.11a provides for a different maximum transmit power output in each U-NII ... If the OFDM signal is received over such a path, then each sub-carrier will ... ftp.linksys.com/products/images/wp_802.asp - 35k - Cached - Similar pages


Factors Causing Uncertainties in Outdoor Wireless Wearable ...

Rain attenuates, scatters, and depolarizes the carrier **signal**. ... is usually maximized to support **maximum** reliability without excessive **transmission power**. ... doi.ieeecomputersociety.org/10.1109/MPRV.2003.1203748 - Similar pages

Google Groups results for signal path maximum transmission power modulation wireless

00

6./ Wireless alarm system techniques (part 1 of 2)... - alt.security.alarms - Nov 06, 2004 <u>Transmission of Remote Video signal</u> - rec.radio.amateur.misc - Jul 03, 1998 <u>Digital Subscriber Line (xDSL) FAQ v19990714</u> - comp.dcom.xdsl - Jul 23, 2000



signal path maximum transmission p

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

Google Home - Advertising Programs - Business Solutions - About Google

©2006 Google